Bauhaus-Universität Weimar
Bauhaus Summer School 2025 – NextGen Engineers

Douglas Daniel Itúrburu | Matej Kozić | Luis León Gil | Douglas Asare Ansah

Under the guidance of M.Sc. Gledson Rodrigo Tondo

# Wind engineering for Long-span Bridges: Flutter Study

## What Exactly is Flutter?

Flutter refers to a phenomenon wherein, above a certain wind speed, a bridge becomes unstable and enters a self-sustaining loop of increasingly violent heaves and twists. This occurs when the effective damping of the structure becomes negative: instead of dissipating vibrational energy, the system amplifies it, leading to infinitely scaling oscillations This is the origin of flutter; a phenomenon that can only be avoided, not stopped or endured.




Fig. 2: Oscillation graphs for heave and pitch with vs without flutter




Fig. 1: Lillebaelt suspension bridge under different frequencies

## Lillaebelt Bridge: Modeshapes and Frequencies

Any given bridge has infinite modeshapes that correspond to different frequencies. However, coupled flutter requires only two; a heave and a pitch modeshape. For this project, we have used the lowest frequencies for both, 0.156 Hertz and 0.499 Hertz respectively, which are the most easily triggered. Their modeshapes are displayed in the above image.

## Computational analysis: 5 methods

In this project, we have used 5 increasingly complex methods to calculate the critical flutter windspeed for the Lillaebelt Bridge.

- Method 1 involved the use of several empirical equations to obtain a rough estimate
- Method 2 simplified the bridge section to a flat plate and obtained its forces & moments
- Method 3 followed method 2´s methodology but properly modelled the full section
- Method 4 simulated the non-linear forces on a 2D slice of the bridge for better accuracy
- Method 5, the most complex and time-consuming, used several slices (5 in our case) and simulated them in pseudo 3D.

***Results Table***

| Method: | Method 1 | Method 2 | Method 3 |
|---|---|---|---|
| Critical Speed | 93.3 m/s | 92.4 m/s | 90.4 m/s |
| **Method:** | **Method 4** | **Method 5** | **Average** |
| Critical Speed | 94.0 m/s | 92.0 m/s | 92.4 m/s |

Table 1: Critical Speed of each method and the average.



Fig. 3: Bridge slices with vs without flutter

## Conclusions

Long-span bridges must be designed to withstand dynamic wind effects, particularly flutter. The combination of numerical simulations, wind tunnel testing, and emerging technologies such as digital twins and artificial intelligence enables safer and more sustainable design. The future of bridge engineering lies in balancing elegance, innovation, and long-term stability.

In our specific case, the studied bridge is well designed. It can withstand a wind speed up to 92 m/s, well over the 71,8 m/s that the Eurocode-1991-1-4 demands.

**Contact:**
Luis León Gil | Student | Universidad Politécnica de Madrid | leongilperera@gmail.com | +34 659 59 59 71
Matej Kozić | Student | Josip Juraj Strossmayer University of Osijek | matejkozic0@gmail.com | +385 981754329
Douglas Asare Ansah | Graduate | Central University | ansahdouglas3468@gmail.com | +233548964886
Douglas Iturburu | Civil Engineer | Catholic University of Guayaquil | douglasiturburu132@hotmail.com | +593980250025