

# Assignment3

## Shaders

Francesco Andreussi  
francesco.andreussi@uni-weimar.de

8 November 2018

### Deadline

Wednesday, 21 November 2018 at 23:55.

### Task

- Extend the `Node` class with a `PointLightNode` class, which has as additional attributes `lightIntensity` and `lightColor`. (10%)
- Assign a different color for each planet using `glUniform3f`. (10%)
- Implement per-fragment Blinn-Phong local illumination model in the planet fragment shader. (50%)
- Comment the code extensively. (10%)
- **Additional Task:** implement a Cel-Shading effect (adding a colored outline to the planets) and allow switching between the two appearances pressing 1 and 2. (20%)

### Tips & Suggestions

- Remember to upload as uniforms the light attributes (position, color and intensity).
- Planets ambient color can be the same as the diffuse color and the specular color can be white.
- Before performing the dot products, both vectors need to be normalized.
- The light should be in the center of the solar system.

- The Cel-Shading (aka Toon Shading) effect consists in a further step of “colour-discretisation” (if  $\text{colour} > \text{threshold}$  then  $\text{m\_colour1}$  else  $\text{m\_colour2}$ ).
- In order to detect a relevant edge you should calculate the dot product between the surface normal and the view direction, if this value is above a threshold assign to that fragment the outlineColour (in this case the relevant outline have normal perpendicular to the view direction).