


P r o c e s s e d

O a s e n

partial final presentation /
grayson daniel bailey



t e c h n i c a l
e x p e r i m e n t a t i o n



e p h e m e r a l
o u t p u t




From this point of view the creations are valuable only when they produce new, previously unknown relationships. This is yet another way of saying that reproduction (repetition of existing relationships) without enriching point of view must from the special point of view of creative art be considered at best only a matter of virtuosity.

aggregatory
build of elements




physical translation
between media

contemporary
technical vision



data inventory
& translation




human relation
to nature & technology



aggregatory fusion
& updated vision







kunsthalle


national theatre

schlemmer apt.


hauptgebäude


tempelherrenhaus


haus am horn





direct locational exchange //
ubiquitous


















aggregate collection & synthesis output //
novel translation between local media






























input
transfer





input
translation




















based image:
DNT




image
processing,
agent-based
drawing
operations





based image:
tempelherrenhaus

*// each location provides
a list of starting points
via motion detection*



mechanical reset per
overlay to allow
continuous roll plotting

drawing operation
overlays from locations,
continuous visual output





A base image is used for analysis

// this image is either periodically
taken of the the site through the day,
or a static image representing the
site in every drawing.



motion detection points are imported
into the processed image

```
// these points are from the webcam  
motion detection operations which  
happen at each site
```

```
// the motion capture points are  
taken periodically from the sites and  
transferred to the drawing machine  
location as data files
```



Image / pixel values are derived from
the image at the imported points


// each location has innate RGB values,
as well as a brightness and saturation

// these values can be used to
influence drawing operations



generative operations begin from the
starting points, based on image data


```
// line and changed path generation  
based on underlying image
```





each set of connected lines has a
number of characteristics

next step location, step size, amount
of steps






step size of path is determined by
brightness of each point:

```
void uploadPoints() {


    File tempFile = new File("C:/Users/grays/Desktop/CODING/PlotterContinuousRun_
        skeleton/motionX_"+saveCount+".txt");
    if (tempFile.exists()) {
        String[] tempHolderX = loadStrings("C:/Users/grays/Desktop/CODING/
            PlotterContinuousRun_skeleton/motionX_"+saveCount+".txt");
        String[] tempHolderY = loadStrings("C:/Users/grays/Desktop/CODING/
            PlotterContinuousRun_skeleton/motionY_"+saveCount+".txt");
        float scale;
        for (int i = 0; i < tempHolderX.length; i++) {
            scale = map(brightness(currentImage
                get(int(tempHolderX[i]),int(tempHolderY[i]))),0,255,5,90);
            swankAgents.add(new SwankAgent(new PVector(int(tempHolderX[i]),
                int(tempHolderY[i])), scale));
        }
    }
}
```





orientation of segment location
determined through blue values:


```
void moveImageDir(float scale) {
    float angle = ((blue(currentImage.get((int)location.x,
        (int)location.y))/255.0))*scale;
    prevLocation = location;
    location = new PVector(location.x + sin(angle)*speed,
        location.y + cos(angle)*speed);
    checkBorder();
    stroke(0);
}
```





number of segments determined by
number of starting points

```
void processImage(int _pen) {
    uploadPoints();
    String[] postDate = loadStrings("C:/Users/grays/Desktop/CODING/
        PlotterContinuousRun_skeleton/postDate_"+saveCount+".txt");
    int runCount = ceil(500/(swankAgents.size()+1));
    if (runCount > 15) runCount = 15;
    beginRecord(hpgl);
    hpgl.selectPen(_pen);
    println(swankAgents.size());
    updateSwank(runCount);
    textSize(15);
    text(postDate[0], width-400, height-20);
    text("N G Z C M | P 3 | 7 4 7 5 A", width-200, height-20);
    endRecord();
    saveCount++;
}
```



of segments



changes in values, changes in
generation:

step size: based on saturation of the img.location

orientation: based on the red of the img.location

number of segments: $600 / (\text{points} + 1)$



changes in values, changes in
generation:

step size: based on red of the img.location

orientation: based on the green of the img.location

number of segments: $500 / (\text{points} + 1)$




changes in values, changes in
generation:


step size: based on brightness of the img.location


orientation: based on the blue of the img.location

number of segments: step size / 10











We cannot therefore express hostility towards representational art but must demand that in conformity with our interest in and feeling for the world at large, up-to-date consequences are drawn:



that painterly methods of representation suggestive merely of past times and past ideologies shall disappear and their place betaken by



mechanical means of representation and their as yet unpredictable possibilities of extension.